

Technical Standard Specification

Series: ATT S-150-48

Medium: Water up to 150 °C

maximum external volume: 10 ltr

max. system pressure: 8 bar + max. pump pressure

Functional equipment hydraulic

- Temperature control unit with heating circuit and cooling circuit, for connection to valve station, for quick commutation between hot circuit and cold circuit
- Temperature-controlled supply of water from process
- Level controlling with automatic level regulation
- Dirt trap in cooling water supply and in return line of circulating system
- Separate automatic filling with dirt trap
- Flow metering according to principle of pressure difference in both circuits
- Monitoring of surface of heating rods by temperature sensor
- System pressure, connection for compressed air required: 6 to 8 bar
- Booster pump type DS 360 for refilling
- Tank: VA; piping: galvanized steel
- Unit on rollers and ready for connection



Functional equipment electrical

- SPS controller with touch screen
- Heating with Incolloy stainless steel tubular heaters
- Heating control by solid-state-relay
- Control cabinet IP54 fan-ventilated
- Electrical wiring to series terminal strips
- Potential-free input for signal for commutation cold/hot (front door)
- Potential-free contact for collective alarm on 3-pin plug (front door)

Optional equipment

- System EcoTemp for intermittent operation
- Connection for ext. temp. sensor PT100 or type J/K
- Remote touch screen with 15 m cable

	Hot circuit	Cold circuit
Heating capacity	48 kW	12 kW
Cooling capacity	220 kW	220 kW
- at 80°C temperature to process	plate heat exchanger	plate heat exchanger
- 15°C cooling water temperature	with solenoid valve	with solenoid valve
- 3 bar cooling water diff. pressure		
Pump	CRI 5-11 (slide ring seal)	CRI 5-11 (slide ring seal)
Output rate (max.)	150 ltr/min	150 ltr/min
Pressure (max.)	7.5 bar	7.5 bar
Motor capacity	2.2 kW	2.2 kW
Construction type	multi-stage centrifugal pump	multi-stage centrifugal pump
Dimensions/weight/colours		
Dimensions L/W/H: (w/o connections)	1,395 mm x 753 mm x 1,180 mm#	
Weight:	approx. 400 kg	
Colour:	case: RAL 7035 light grey	
	front door: RAL 7016 anthracite grey	
Connections		
Circulating medium	flange DN32/PN16 (DIN EN 1092-1)	
Separate filling	hose nipple 14 mm	
Cooling water	sealing cone DIN 3863 G1 ext. thr.	
Compressed air	hose nipple 14 mm	
Accessories		
	4 pieces	corrugated metal hose NW 32, length 3 m, connec. flange DN32/PN40-DIN EN 1092-1 (part No. 21661)
	1 piece	compressed air hose R 3/8, 4 m (part No. 03644)

- Subject to technical changes; latest update: April 25th, 2016; changed by F.Spork -

This unit complies with the European Directives. Other directives and standards are met only if they listed in the order confirmation. This technical specification represents the standard equipment. For non-standard specifications upon customer's request see quotations or O/Cs. In case of contradictory information the quotation or O/C applies.

Technical Standard Specification

Series: ATT S-180-48
or ATT S-180-60

maximum external volume: 7 ltr

Medium: Water up to 180°C

max. system pressure: 14 bar + max. pump pressure

Functional equipment hydraulic

- Temperature control unit with heating circuit and cooling circuit, for connection to valve stations, for quick commutation between hot circuit and cold circuit
- Temperature-controlled supply of water from process
- Level controlling with automatic level regulation
- Dirt trap in cooling water supply and in return line of circulating system
- Separate automatic filling with dirt trap
- Flow metering according to principle of pressure difference in both circuits
- Monitoring of surface of heating rods by temperature sensor
- System pressure control with pressure booster, connection for compressed air required: 6 to 8 bar
- Booster pump type DS 360 for refilling
- Corrosion resistant components (VA, MS)
- Unit on rollers and ready for connection



Functional equipment electrical

- SPS controller with touch screen
- Heating with Incolloy stainless steel tubular heaters
- Heating control by solid-state-relay
- Control cabinet IP54 fan-ventilated
- Electrical wiring to series terminal strips
- Potential-free input for signal for commutation cold/hot (front door)
- Potential-free contact for collective alarm on 3-pin plug (front door)

Optional equipment

- System EcoTemp for intermittent operation
- Connection for ext. temp. sensor PT100 or type J/K
- Remote touch screen with 15 m cable

	Hot circuit	Cold circuit
Heating capacity	48 kW or 60 kW	12 kW
Cooling capacity	52 kW	220 kW
- at 80°C temperature to process	tube bundle heat exchanger	plate heat exchanger
- 15°C cooling water temperature	with solenoid valve	with solenoid valve
- 3 bar cooling water diff. pressure		
Pump	CRI 5-11 (slide ring seal)	CRI 5-11 (slide ring seal)
Output rate (max.)	150 ltr/min	150 ltr/min
Pressure (max.)	7.5 bar	7.5 bar
Motor capacity	2.2 kW	2.2 kW
Construction type	multi-stage centrifugal pump	multi-stage centrifugal pump

Dimensions/weight/colours

Dimensions L/W/H: 1,395 mm x 753 mm x 1,180 mm
(w/o connections)

Weight: approx. 400 kg

Colour: case: RAL 7035 light grey
front door: RAL 7016 anthracite grey

Connections

Circulating medium	flange DN32/PN16 (DIN EN 8434-1)
Separate filling	hose nipple 14 mm
Cooling water	sealing cone DIN 3863 G1 ext. thr.
Compressed air	hose nipple 14 mm

Accessories	4 pieces	corrugated metal hose NW 32, length 3 m, conn. flange DN32/PN40 - DIN EN 1092-1 (part No. 21661)
	1 piece	compressed air hose R 3/8, 4 m (part No. 03644)

- Subject to technical changes; latest update: June 29th, 2016; changed by U.Hoferer -

This unit complies with the European Directives. Other directives and standards are met only if they listed in the order confirmation. This technical specification represents the standard equipment. For non-standard specifications upon customer's request see quotations or O/Cs. In case of contradictory information the quotation or O/C applies.